



DODSO 1E (SID) RNAV GNSS RWY 02L - DESCRIPTIONS

Formal & Abbreviated Descriptions

| Formal Description                                      | Abbreviated Description  | Path Terminator | Fly-Over required |
|---------------------------------------------------------|--------------------------|-----------------|-------------------|
| To MOLVO on course 023° at or above 2000ft, turn right. | MOLVO [M023; A020+; R] - | CF              | N                 |
| To EMRIX at or above 4000ft.                            | EMRIX [A040+] -          | TF              | N                 |
| To HOSBA at or above 7000ft, turn left.                 | HOSBA [A070+; L] -       | TF              | N                 |
| To VEBMA.                                               | VEBMA -                  | TF              | N                 |
| To TOMAN.                                               | TOMAN -                  | TF              | N                 |
| To DODSO.                                               | DODSO                    | TF              | N                 |

Tabular Descriptions

| Path Term | Waypoint Name | Fly-Over | Course °M(°T) | Distance (NM) | Turn Direction | Altitude | Speed Limit | Navigation Spec |
|-----------|---------------|----------|---------------|---------------|----------------|----------|-------------|-----------------|
| CF        | MOLVO         | -        | 023(023.4)    | 8.0           | R              | A020+    | -           | RNAV1           |
| TF        | EMRIX         | -        | 114(114.4)    | 9.0           | -              | A040+    | -           | RNAV1           |
| TF        | HOSBA         | -        | 114(114.4)    | 15.0          | L              | A070+    | -           | RNAV1           |
| TF        | VEBMA         | -        | 088(088.4)    | 29.0          | -              | -        | -           | RNAV1           |
| TF        | TOMAN         | -        | 088(088.4)    | 54.0          | -              | -        | -           | RNAV1           |
| TF        | DODSO         | -        | 088(088.4)    | 27.0          | -              | -        | -           | RNAV1           |

Radio Communications Failure Procedure

|   |                                                                                                                                                                                                                                   |
|---|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 | SET TRANSPONDER TO MODE A/C CODE 7600                                                                                                                                                                                             |
| 2 | COMMUNICATIONS FAILURE OCCURS IMMEDIATELY AFTER DEPARTURE:<br><br>PROCEED DIRECT TO NYLON HOLDING AREA (NHA) CLIMBING TO THE LAST ASSIGNED ALTITUDE, THEREAFTER REFER TO SINGAPORE AIP ON RADIO COMMUNICATIONS FAILURE PROCEDURE. |