

DODSO 1A (SID) RNAV GNSS RWY 02C - DESCRIPTIONS**Formal & Abbreviated Descriptions**

| Formal Description | Abbreviated Description | Path Terminator | Fly-Over required |
|---|--------------------------|-----------------|-------------------|
| To MOXIB on course 203° at or above 2000ft, turn right. | MOXIB [M203; A020+; R] - | CF | N |
| To EMRIX at or above 4000ft. | EMRIX [A040+] - | TF | N |
| To HOSBA at or above 7000ft, turn left. | HOSBA [A070+; L] - | TF | N |
| To VEBMA. | VEBMA - | TF | N |
| To TOMAN. | TOMAN - | TF | N |
| To DODSO. | DODSO | TF | N |

Tabular Descriptions

| Path Term | Waypoint Name | Fly-Over | Course °M(°T) | Distance (NM) | Turn Direction | Altitude | Speed Limit | Navigation Spec |
|-----------|---------------|----------|---------------|---------------|----------------|----------|-------------|-----------------|
| CF | MOXIB | - | 023(023.4) | 8.0 | R | A020+ | - | RNAV1 |
| TF | EMRIX | - | 114(114.4) | 8.0 | - | A040+ | - | RNAV1 |
| TF | HOSBA | - | 114(114.4) | 15.0 | L | A070+ | - | RNAV1 |
| TF | VEBMA | - | 088(088.4) | 29.0 | - | - | - | RNAV1 |
| TF | TOMAN | - | 088(088.4) | 54.0 | - | - | - | RNAV1 |
| TF | DODSO | - | 088(088.4) | 27.0 | - | - | - | RNAV1 |

Radio Communications Failure Procedure

| | |
|---|--|
| 1 | SET TRANSPONDER TO MODE A/C CODE 7600 |
| 2 | COMMUNICATIONS FAILURE OCCURS IMMEDIATELY AFTER DEPARTURE: PROCEED DIRECT TO NYLON HOLDING AREA (NHA) CLIMBING TO THE LAST ASSIGNED ALTITUDE, THEREAFTER REFER TO SINGAPORE AIP ON RADIO COMMUNICATIONS FAILURE PROCEDURE. |