

STANDARD ARRIVAL CHART
RNAV (GNSS) -
INSTRUMENT (STAR)

ACC 134.4
 APP 124.05
 119.3
 TWR 118.6 / 118.25

TRANSITION ALTITUDE
 11 000ft

D-ATIS AP ID-WSSSS
 128.025

SINGAPORE/Singapore Changi
RWY 20R/C/L
REPOV TWO BRAVO ARRIVAL
REPOV 2B

ELEV, ALT IN FEET
 BEARINGS, TRACKS AND
 RADIALS ARE MAGNETIC
 VAR 0°23'E (2020)

DISTANCES IN NM

CAUTION: RWY 02R/20L CLOSED UNTIL FURTHER ADVISED

NOTE: RADAR REQUIRED

NOTE: RNAV-1 NAVIGATION SPECIFICATION GNSS REQUIRED

NOTE: REFER TO BACK PAGE FOR
 - FORMAL AND TABULAR DESCRIPTIONS
 - RADIO COM FAILURE PROCEDURES

TEKONG
 DVOR/DME 116.5
 VTK 
 01° 24' 55"N
 104° 01' 20" E
 60m

CAUTION
RWY 02R/20L CLOSED
UNTIL FURTHER ADVISED

DOVAN
 01° 19' 38" N
 104° 12' 49" E
 Cross 4000ft or abv

BITAM
 01° 08' 13" N
 104° 07' 57" E
 Cross 7000ft or abv

REMES
 00° 43' 42" N
 103° 57' 35" E
 IAS 220kts

REPOV
 00° 16' 23" N
 104° 03' 00" E
 Cross FL210 or blw
 IAS 250kts

NYLON
 01° 36' 57" N
 104° 06' 24" E

A030 - F140
 Max 220kts (IAS)
 1 min

BIPOP
 01° 31' 22" N
 104° 10' 18" E
 Cross 3000ft or abv
 IAS 190kts

A060 - F140
 Max 220kts (IAS)
 1 min

F150 - F250
 Max 250kts (IAS)
 1.5 min

